E3250 230/115V 50HZ HUK

ENERGY AT FAIR PRICE

ULS ULTIMATE LIFTING SOLUTIONS
TEL: 01384 986 026
WWW.ULSLIFTING.COM



Simple professional generator. Pramac has designed this generator to ensure a high performance level at attractive price. Powerful and strong generator; easy to maintain, it will be soon essential to all your activities.

Main Features		
Frequency	Hz	50
Voltage	V	230/115
Power factor	cos ϕ	0.9
Phase		1

Power Rating		
Standby power LTP	kVA	2.9
Standby power LTP	kW	2.6
Continuous power COP	kVA	2.5
Continuous power COP	kW	2.2

Ratings definition (According to standard ISO8528 1:2005)
COP - Continuous Power: It is defined as being the maximum power which a generating set is capable of delivering continuously for an unlimited number of hours, with the maintenance intervals and procedures being carried out as prescribed by the manufacturers.
LTP - Limited-Time running Power: It is defined as the maximum power available, under the agreed operating conditions, for which the generating set is capable of delivering for up to 500 h of operation per year (whose no more than 300 for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. No overload capability is available.

www.pramac.com

Engine specifications		
Engine Brand		Honda
Model		GX160
Engine cooling system		Air
Displacement	cm^3	163
Aspiration		Natural
Operating Speed-Nominal	rpm	3000
Speed governor		Mechanical
Fuel		Petrol
Oil capacity	l	0.6
Starting system		Recoil



Alternator Specifications		
Type		
Class		H
IP protection		23
Poles		2
Frequency	Hz	50
Voltage regulation system		Capacitor

Dimensional data		
Length	(L) mm	625
Width	(W) mm	455
Height	(H) mm	455
Dry weight	Kg	38
Fuel tank capacity	l	3.1

Autonomy		
Fuel consumption @ 75% PRP	l/h	0.88
Fuel consumption @ 100% PRP	l/h	1.17
Running time 75% PRP	h	3.52
Running time 100% PRP	h	2.65

Noise level		
Guaranteed noise level (LWA)	dB(A)	94
Noise pressure level @ 7 m	dB(A)	66

www.pramac.com

ULS ULTIMATE LIFTING SOLUTIONS
TEL: 01384 986 026
WWW.ULSLIFTING.COM

GENSET CONTROL



COMMANDS
- Selector switch: OFF - ON
- Starting systems: Recoil
- Selector swith 115/230V
- Fuel Cock

PROTECTIONS STANDARD
- Thermal protection
- Oil Guard

SOCKET TYPE

2P+T CEE 115V 16A IP44	1
2P+T CEE 230V 16A IP44	1

www.pramac.com

Official UK PRAMAC Distributor

ULS ULTIMATE LIFTING SOLUTIONS

TEL: 01384 986 026
WWW.ULSLIFTING.COM

The information is aligned with the Data file at the time of download. Printed on 25/09/2021 (ID 2348)

©2021 | PR INDUSTRIAL s.r.l. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice

PRAMAC