

**ET 200 N Standard equipment**

- ✓ Work positioning lever
- ✓ IP67 plug
- ✓ Trolley available for use with a gantry
- ✓ Upper limit safety device
- ✓ Direct control with 3-pushbutton IP65 1.5m pendant control
- ✓ Self-braking motor with magnetic device

**Applications**

Ideal for operations that do not require bracket extension.


**DRUM WITH TWO FIXED TURNS OF STEEL ROPE**

To warrant higher machine reliability and longer life, the drum is built with a special patented device, which when the metal rope is completely unwound, keeps two turns always wound. This prevents straining the rope attachment point on the drum.

**110V/50HZ**
**230V/50HZ**
**MOTOR AVAILABLE**
**✓ ET 200 N**

**TEL: 01384 986 026**
**WWW.ULSLIFTING.COM**

ET 200N		
Maximum capacity	kg	200
Av. full load lifting speed	m/min	19
Max. working height	m	30
Ø wire rope	mm	5
Rope length	m	31
Motor power rate 230V/50Hz 110V/50Hz	kW	0.75
Motor speed min./max.	rpm	1350
Running current	A	14
Machine weight	kg	39
SPL in operator's position	dB(A)	<70
Dimensions w/l/h	mm	330/770/520
Packing dimensions w/l/h	mm	350/820/500